Connected Pro Series



MODEL 3124H Belt or Chain Drive Garage Door Opener Battery Backup Capable



# Highlights

- Smart Garage Capabilities Integrated Wi-Fi provides multiple benefits such as:
  - » Security Instantly know if someone is operating your garage door without permission.
  - » Convenience Open your door for family members, deliveries or service providers from anywhere with your smart device.
- » Safety Have garage door automatically close at a specific time or after an elapsed time period in case it's left open.
- Quiet, strong performance 140 volt DC motor provides quiet yet strong performance with an opening speed of 7.5" per second\*. Opener works on residential sectional garage doors up to 14' high, and one-piece doors up to 8' high.
- Battery Backup Capable (Model 3124H-B)— Don't get locked outside the garage when the power goes out! The optional battery unit can easily be added to your opener.

THE GENIE STORY: Genie has a rich history in developing garage door openers that feature reliability, strength, safety, security, and convenience. Since 1954, Genie has produced millions of openers that serve millions of satisfied homeowners every day of every year. Shouldn't you have one in your garage? Genie — The Brand You Trust.

- GenieSense<sup>™</sup> Monitoring Automatic force profiling and diagnostic technology improves safety by stopping operation when significant changes occur.
- Soft Start and Stop Control DC technology allows your door to begin and end its movement smoothly instead of abruptly whenever you operate it, creating less noise and less wear on the door.
- **Power on Demand** Refers to the ability of the opener to continually monitor the door's travel and deliver just the right amount of power for smooth and consistent movement.
- Dependability A Limited Lifetime Warranty<sup>®</sup> on the motor and integrated gearbox shows how confident Genie is that your opener will perform when you need it to for years to come.

\*\*+/- 05" per second for sectional doors.
\*\*\* When compared to industry standard, 12V motors
0 Limited non-transferable warranty. See Programming, Operation and Maintenance manual for detail

# Connected Pro Series

# **Standard Equipment and Warranty**



# **Features and Benefits**

# POWER AND CONTROL

**DC Motor Smart Technology** – The DC motor provides quiet operation as well as Soft Start and Stop control. This means the door begins and ends its travel smoothly, not abruptly, which lessens noise as well as wear and tear on the garage door.

**C-Channel Rail** – Strong rail design helps promote durability and safety. Also conceals the belt (or chain) for better appearance.

Speed - Opening speed of 7.5 inches/second\* gets you on your way faster.

## SAFETY

**Safe-T-Beam® Non-Contact Reversing System** – When objects pass through the infrared beam, the garage door automatically stops closing and reverses to open without having to make physical contact with the door.

## SECURITY

Intellicode® Access Security System – Prevents thieves from using unauthorized remotes to open your door by always selecting a new code from billions of combinations each time the opener is operated.

**Sure-Lock<sup>™</sup> Control** – Allows you to lock out remote controls and wireless keypad at any time for increased security – also known as a vacation lock.

# CONVENIENCE

**Smart Lighting** – Light bulbs are positioned toward inside of garage instead of toward door for light where it's needed most. Lights stay on for 4 minutes once opener is activated for ample time to get into house. Opener features bright lighting with (2) bulb capability. Genie branded LED light bulbs recommended. (If incandescent bulbs used, 100 watt max per bulb). See Genie LED bulb this page for additional details.

**Auto-Seek Dual Frequency** – The opener automatically uses either 315 or 390 MHz frequency to avoid potential nearby interference, such as military base equipment, to help ensure the opener operates properly.

**Pre-Programmed Remote** – Ready to use out-of-the-box with simple steps to change the programming if so desired.

**HomeLink® and Car2U® Compatible** – Works with current and ALL previous versions of HomeLink® or Car2U<sup>®</sup>. No additional external repeater kit or compatibility bridge needed.

6' Power Cord – For high ceiling applications.

CALIFORNIA RESIDENTS – This opener has the option to add battery backup. As required by SB-969, all newly installed openers must have battery backup as of 7///19. To order this opener with battery backup, refer to Model 3124H-B. If needed, visit www.geniecompany.com or ask your Genie dealer for details.

#### ¢ Limited non-transferable warranty. See Programming, Operation and Maintenance manual for details.



#### The Genie Company • One Door Drive, Mt. Hope, Ohio 44660 1.800.35.GENIE (354-3643) • www.geniecompany.com Item 6001.3124 2/21

# Aladdin Connect® INTEGRATED Wi-Fi CONNECTIVITY

Remotely monitor and control your garage door from almost anywhere with your smart device. Time-based features allow you to set door to automatically close and/or notify after a set length of time; as well as schedule a specific hour and minute to close the door and/or notify when it does. Also allows for multiple individual user accounts so you can provide virtual key access for your garage door to a friend, relative, or service person for a certain time, a range of time, or permanently.

Use the Aladdin Connect app to control any combination of 20 different Genie Wi-Fi integrated garage door openers or standalone Aladdin Connect Door Control Modules.

# **Convenience Options**

# Genie<sup>®</sup> Garage Door Opener LED Bulb

Common LED and CFL bulbs can emit interference to limit the range of garage door remotes. Incandescent light bulbs, which are being phased out due to energy inefficiency, can have their lives shortened by vibration associated with opener operation. The Genie LED bulb solves these and other problems to ensure the garage door opener light doesn't leave your garage in the dark!

#### **Wireless Keypad**

HEAVIER DOORS

Easy-to-program keypad mounts outside your door to give you convenient code access to your garage, which is great when you are outside without the remote control. Back-lit keypad lets you easily see the numbers and control up to 3 openers. Uses Auto-Seek Dual Frequency (315/390 MHz).



Choose a color for the flip-up cover that best complements your home. White is standard, other colors sold separately.

Battery Backup (Model 3124H-B) Add this option and if the power goes out, Genie battery backup power goes on so you don't have to manually open and close the garage door!

## 1-Button Remote

Simple yet versatile one-button remote features auto-seek dual frequency. Can be used on a keychain or as a traditional visor style remote. Backward compatible with all Intellicode® equipped Genie garage door openers.

#### Wireless Wall Console

An attractive wall console that's completely wireless for flexible placement in the garage. Features an optional pulsing back-light as well as delay button that gives ample time (up to 30 seconds) to exit the garage before the door begins moving. The work light button can turn just the opener's light on at any time. Compatible with most Genie Intellicode® openers made since 2013.



## **Heavy-Duty Rail**

Heavy-duty design prevents rail deflection ensuring smooth movement on taller garage doors. The rail rigidity can also improve the aesthetics of door travel itself.

YOUR GENIE PROFESSIONAL DEALER:

© 2021 The Genie Company. Genie, IntelliG, ReliaG, Safe-T-Beam, Intellicode, Aladdin Connect, GenieMaster and the Genie logo are registered trademarks and Illuminator and Sure-Lock are trademarks of GMI Holdings, Inc., d/b/a The Genie Company. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation. HomeLink is a registered trademark of Gentex Corporation. Car2U is a registered trademark of Lear Corporation. | © 2021 Google LLC All rights reserved. Google Assistant and Google Play are trademarks of Google LLC. | Amazon, Echo, Alexa, and all related logos are trademarks of Amazon.com Inc. or its affiliates.



