

Richards-Wilcox

Engineered For Life

WHEN EVERY SECOND COUNTS



SLIDETITE 2.0 FOUR-FOLD DOORS

Ideal for

- Fire Halls
- Emergency Medical Services (EMS)
- Light Rail Vehicles (LRV)
- Transit Facilities
- Restaurants and Cafés

- Auto Dealerships
- Sallyports
- Security Gates
- Parking Garage Gates
 - ...And many more applications!















WHAT SETS SLIDETITE 2.0 A PART?







AESTHETICS

The Slidetite™ 2.0 has an aluminum retainer that snaps in place. The interior door face has absolutely no fasteners, giving the door a clean and professional look. Large factory-installed glazing creates an abundance of natural light.

LIFE CYCLE

Slidetite[™] 2.0 doors are engineered to operate for well over a million cycles. It's designed for a longer life with minimal maintenance required.



SAFETY

Slidetite™ 2.0 has been designed to minimize pinch hazards providing you, not only the highest performing four-fold solution, but a safe one as well.



THERMAL EFFICIENCY

Opens and closes twice as fast as sectional doors. This minimizes heat loss. Optional insulated tubular framing is available. You can also replace windows with insulated paneling to increase R-Value.



MANUAL OPERATION

Has the ability to disengage and reengage from floor level, for manual operation at any point in the cycle. This is an advantage available only on Slidetite™ 2.0 doors.

SUPERB STANDARD FEATURES

MOUNTING

INTERIOR

Interior Mounted Slidetite™ 2.0 doors are substantially less invasive than traditional sectional doors. It doesn't impede on other elements of the building's construction.



EXTERIOR

When space is a problem, Exterior mounting is the solution. Perfect for the retro-fit market.

Slidetite 2.0 features a Pre-Assembled Vertical Jamb and Header that ensures the door will fit perfectly in the opening.

PERIMETER DOOR SEALING SYSTEM

WEATHERLOCK™ SEAL SYSTEM

Thermally efficient and unique complete door sealing system is designed for the harshest climates.

The Arctic Grade extruded neoprene perimeter door seal is engineered to seal out dirt, bugs, wind, snow and water and match up beautifully with most door styles and colors. Low-maintenance & one-time installation.

The bristle-based bottom seal, that screws to the door, provides industry-leading insulation that conforms to any floor.



A UNIVERSE OF OPTIONS



COLOURS

- RAL PPG
- Sherwin Williams
- Spectro Match
- Special Custom to Facade



WINDOWS

Various glass types to meet all your needs. Fully customizable.



CONTROLS/ACTIVATION DEVICES

Safety Edges – Comes Standard Photo Eyes – Comes Standard Radio Controls, Loop Detectors & more!

SIMPLY PUT NOTHING COMES CLOSE



SLIDETITE™ 2.0 158 SERIES

1-5/8" Thick Sections

Low Wind load Max Width: 18'-4" Max Height: 14'-9"

FBC, HVHZ, TDI Certifications Pending



SLIDETITE™ 2.0 238 SERIES

2-3/8" Thick Sections

Wind Load: Up to 50psf Max Width: 17'-4" Max Height: 33'-4"

FBC, HVHZ, TDI Certifications Pending



SLIDETITE™ 2.0 400 SERIES 'HURRICANE RATED

4" Thick Sections

Wind Load: Up to 120psf Max Width: 14'-0" Max Height: 16'-0"

FBC, HVHZ, TDI Certifications Pending

MODEL #	SECTION THICKNESS	OPERATION	MOUNT	OPENING
AFFD158	1-5/8"	Electric	Interior	Max Width 18'-4" Max Height 14'-9"
AFFD158E	1-5/8"	Electric	Exterior	
AFFD158H	1-5/8"	Hydro-Pneumatic	Interior	
MFFD158	1-5/8"	Manual	Interior	
MFFD158E	1-5/8"	Manual	Exterior	
AFFD238	2-3/8"	Electric	Interior	Max Width 17'-4" Max Height 33'-4"
AFFD238E	2-3/8"	Electric	Exterior	
AFFD238H	2-3/8"	Hydro-Pneumatic	Interior	
MFFD238	2-3/8"	Manual	Interior	
MFFD238E	2-3/8"	Manual	Exterior	
AFFD400	4"	Electric	Interior	Max Width* 14'-0" Max Height* 16'-0"
AFFD400E	4"	Electric	Exterior	
AFFD400H	4"	Hydro-Pneumatic	Interior	

For more information or a detailed job specification, please contact your local RICHARDS-WILCOX dealer.



5100 Timberlea Boulevard, Mississauga, Ontario Canada L4W 2S5

Toll Free: 1 (800) 667-1572 | Telephone: (905) 625-0037 Fax: (905) 625-0057 | Email: info@rwdoors.com

www.rwdoors.com

Professionally installed and serviced by: